



ATHENS: V. MOIRA, INDUSTRIAL AREA MANDRA, 19600, ATHENS, GREECE, TEL.: +30 210 5557579, FAX: +30 210 5558482 THESSALONIKI: 10th km N.R THESSALONIKIS-POLIGIROU, 57001, THERMI THESSALONIKI, GREECE, TEL.: +30 2310 467275, FAX: 2310 463442

Gavazzi[®] 1244 - A

Alkaline-resistant fiberglass mesh for floors

Fields of application

- Industrial floors and cement slurries
- Prevents cracks in areas where different materials are met
- Enhances cement mortars and other facings with thick granulometry.
- Floors with ground heating
- Enhancement of Gunite

Properties	1	Advantages	

- Flexible
- Wide mesh width (4x4cm), that allows sand and gravel easily to flow through
- 100% glass fiber
- Doesn't rot or rust over time
- Easily applied
- Significantly lower weight compared with conventional iron nets

Mesh width	4X4cm
Weight of unfinished mesh (ISO 3374)	130gr/m ² ±10%
Weight of finished mesh (ISO 3374)	175gr/m ² ±10%
Resistance to tensile strength (ISO 4606)	Warp: 2100N/5cm Weft: 2300N/5cm
Elongation at break (ISO 4606)	Warp: 4,0% [±] 1% Weft: 5,0% [±] 1%
Packing	Rolls of 50X1m or pallet of 16 rolls (800m ²)

The information supplied in this datasheet, concerning the uses and the applications of the product, is based on the experience and knowledge of NEOTEX[®] SA .It is offered as a service to designers and contractors in order to help them find potential solutions. However, as a supplier, NEOTEX[®] SA does not control the actual use of the product and therefore cannot be held responsible for the results of its use. As a result of continual technical evolution, it is up to our clients to check with our technical department that this present data sheet has not been modified by a more recent edition.